

# SYSTEM gaZalarm

## FACILITY CARD

### PRODUCT DESCRIPTION

The facility card forms part of gaZalarm control family and provide field wiring facilities for sensor and remote inputs, analogue outputs, power in/out and relay out. Each group of 12 PI 00 cards require facility card.

The options for relay outputs provide flexibility in system design to suit the application requirements.

#### FEATURES:

- ◆ Sensor Interface
- ◆ Relay options
- ◆ Support all alarm functions
- ◆ Remote inhibit/reset facility
- ◆ Accepts up to 2.5mm<sup>2</sup> cable
- ◆ Push buttons:
  - ◆ ACCEPT: for Audio Alarms Acknowledge
  - ◆ RESET: To reset the visual alarm status
  - ◆ LAMP: to test the LED's working status



#### INTERFACE CARDS:

- ◆ Double SPDT relay card
- ◆ 3 single pole, changeover relays (A1, A2, F)

### General Specifications

<ul style="list-style-type: none"> <li>➤ <b>Relay Contacts:</b> 5A at 250Vac/32Vdc (non-inductive)</li> <li>➤ <b>Relay Operation:</b> Selectable latching/non-latching Normally energized/ de-energized</li> <li>➤ <b>Power:</b> Field Interface card 0.0W Double SPDT card 0.8W Triple SPDT card 1.0W</li> <li>➤ <b>Terminals:</b> Accepts up to 2.5mm<sup>2</sup> (14AWG) cable</li> </ul>	<ul style="list-style-type: none"> <li>➤ <b>Operating Temperature:</b> -20°C to 65°C</li> <li>➤ <b>Operating Humidity:</b> 20 to 99%, non-condensing</li> <li>➤ <b>Storage Temperature:</b> -20°C to 85°C</li> </ul>
--	--

Note: We reserve the rights to modify the design & specs or stop the production of above said system