

The toughest CGI on the market!

- ► Large Backlit Display Can Show Up To 4 Gases
 - Combustibles LEL and %Gas and Optional PPM
 - Oxygen
 - Carbon Monoxide
 - Hydrogen Sulfide
- ➤ Weather Resistant Design
- ► Internal Pump
- **►** Infrared Downloading
- ► Lowest Cost, Long Life Sensors
- **► LED Warning Lights**
- ➤ Durable Stainless Steel Housing
- ► Loud Audible Alarm



TRAK-IT®III CGI with its durable design and easy operation will make finding gas leaks fast and accurate. The bright LCD display shows all gas concentrations simultaneously fulfilling any confined space entry requirements. A bar-hole test feature helps accurately locate below ground leaks. High resolution display (0.1% LEL) in combination with the high volume rotary pump helps to quickly locate hard to find leaks.

Calibration is easily accomplished in the field with **TRAK-IT®III CGI**. The high-tech sensors provide a long life with the lowest replacement cost. **TRAK-IT®III CGI** has the lowest cost of operation of any instrument in its class.

When it comes to locating or pinpointing gas leaks and monitoring confined spaces, You can depend on the Trak-It®III CGI to provide the safety and accuracy you need.

STANDARD FEATURES

Internal Pump Water/Dust Filter **Push Button Operation** Field Calibration Date/Time Display **Operation Memory** Calibration Memory Infrared Download Audible/Visual Alarms **Backlit LCD** Probe Assembly

Programmable Auto Shut Off

Padded Carry Pouch

OPTIONS

Optional PPM Printer PC Interface



Approved UL913, For Class 1, Division 1, Groups D Hazardous locations when used with alkaline batteries.

Calibration Kit PADDED _ CARRY POUCH LARGE, EASY TO IR WINDOW READ DISPLAY (DOWNLOADING) SPEAKER STATUS/ALARM LEDS LUFR PROBE NECK STRAP

SENSING FEATURES

TRAK-IT®III CGI INSTRUMENTS	% LEL DISPLAY	/ %GAS DISPLAY	CARBON MONOXIDI		HYDROGE SULFIDE
TRAK-IT®III CGI-EX Part #T300800-A	•	•			
TRAK-IT®III CGI-EX CO Part # T300800-B	•	•	•		
TRAK-IT®III CGI-EX <i>Plus</i> Part # T300800-C	•	•		•	
TRAK-IT®III CGI-EX/TOX Part # T300800-D	•	•			•
TRAK-IT®III CGI-EX CO <i>Plus</i> Part # T300800-E	•	•	•	•	
TRAK-IT®III CGI-EX/CO/TOX Part # T300800-F	•	•	•		•
TRAK-IT®III CGI-EX TOX <i>Plus</i> Part # T300800-G	•	•		•	•
TRAK-IT®III CGI-4GAS Part # T300800-H	•	•	•	•	•

SENSOR SPECIFICATIONS							
TYPE	RESOLUTION	RANGE	ACCURACY				
PPM	1-10ppm***	0-2000ppm	±10%				
LEL	0.1%*	0-50% LEL	±10%				
%GAS	0.1%	2.5-100%	±5%				
O 2	0.1%	0-25%	±0.2% or 2%**				
CO	1ppm	0-2000ppm	±5ppm or 5%**				
H 2 S	1ppm	0-100ppm	±1ppm or 5%**				
* % gas only display has 0.01% resolution in LEL range							
O 2 CO	0.1% 1ppm 1ppm	0-25% 0-2000ppm 0-100ppm s 0.01% resolution	±0.2% or 2 ±5ppm or 3 ±1ppm or 3 in LEL range				

** Whichever is greater *** Factory set option

PRODUCT SPECIFICATIONS

Size: 6.5" x 4" x 4.25" (16.5 x 10.2 x 10.8cm)

2.8 pounds (1.27 Kg) Weight:

-20 to 120° F (-28.9°C to 48.8°C) Operational Temp: Storage Temp: -20 to 132° F (-28.9°C to 55.5°C) Battery Life: Alkaline: 20 Hrs. continuous

APPLICATIONS

Confined Space Monitoring Vessel Testing Manhole Entry Vault Entry Leak Detection

Leak Pinpointing Pipeline Purging

Distributed by

USERS

Utilities

Maintenance Departments Fire Departments Water/Sewer Departments

Utility Contractors Industrial Plants

FOR MORE INFORMATION J And N Enterprises, Inc.

OPERATIONAL BUTTONS

851 Transport Drive Valparaiso, IN 46383-8432 Phone: (888) 4SENSIT (473-6748) (219) 465-2700

Fax: (219) 465-2701 www.gasleaksensors.com

